

- KOMPAK **4-STROKE ENGINES** equipped with low oil level alarm with automatic engine shutdown.
- Air-cooled **OHV OVERHEAD VALVES**.
- 100% copper **ALTERNATOR** equipped with

## AVR.

- Easy start.
- Low maintenance and consumption.
- **MANTENANCE-FREE BATTERY** included in models K10000E and K10000TE.

- **DIGITAL HOUR METER.**
- **WHEEL KIT INCLUDED** in all models.



## K4000S

**3,8 KW**

**50 KG**



## K10000E

**8,0 KW**

**95 KG**



## K10000TE-T

**10 KVA**

**95 KG**



| MODELS                         | K4000S         | K8000          | K10000E         | K10000TE-T                    |
|--------------------------------|----------------|----------------|-----------------|-------------------------------|
| RATED POWER                    | 3,0 kW         | 6,5 kW         | 7,5 kW          | 9,4 kVA (400) / 6,75 kW (230) |
| MAXIMUM POWER                  | 3,3 kW         | 7,0 kW         | 8,0 kW          | 10 kVA (400) / 7,2 kW (230)   |
| VOLTAGE                        | 230 V          | 230 V          | 230 V           | 400 V / 230 V                 |
| OUTPUT SOCKETS                 | 2 schuko 16A   | 1x16A/1x32A    | 1x16A/1x32A     | 1xPCE5P (32A) / 1x32A (230)   |
| HOURLY METER                   | Digital        | Digital        | Digital         | Digital                       |
| RATED AMPERAGE                 | 14,3 A         | 28,3 A         | 32,6 A          | 10,8 A                        |
| ENGINE                         | 4-stroke       | 4-stroke       | 4-stroke        | 4-stroke                      |
| MODEL                          | K220           | K420           | K460            | K460                          |
| CYLINDER CAPACITY              | 223 cc         | 420 cc         | 459 cc          | 459 cc                        |
| POWER                          | 7,0 Hp         | 15 Hp          | 16 Hp           | 16 Hp                         |
| START                          | Manual         | Manual         | Manual/Electric | Manual/Electric               |
| ALTERNATOR TYPE                | Brushes        | Brushes        | Brushes         | Brushes                       |
| BATTERY                        | -              | -              | 14 Ah           | 14 Ah                         |
| ALTERNATOR                     | 100% copper    | 100% copper    | 100% copper     | 100% copper                   |
| POWER FACTOR                   | 1              | 1              | 1               | 0,8 / 1                       |
| VOLTAGE REGULATION             | AVR            | AVR            | AVR             | AVR                           |
| FUEL TANK CAPACITY             | 15 L           | 25 L           | 25 L            | 25 L                          |
| AUTONOMY AT 50% OF THE LOAD    | 14 H           | 13 H           | 12,5 H          | 12,5 H                        |
| SOUND LEVEL AT 7 MTS (DBA) 75% | 68             | 72             | 72              | 72                            |
| DIMENSIONS                     | 715x470x507 mm | 852x570x642 mm | 852x570x642 mm  | 852x570x642 mm                |
| WEIGHT                         | 50 Kg          | 90 Kg          | 95 Kg           | 95 Kg                         |